Product data sheet 5111-3 CT EAN-No. 4000896235384



Length: 375 mm · Torque range min-max: 20 – 120 Nm · Accuracy: 3 % · ■ 36



- · User-friendly reversible ratchet
- Slim ratchet head ideally suited for use on motorcycles
- SYSTEM 5000-3 CT -
- Accuracy ± 3% of the scale value (in direction of actuation for right-hand tightening) (5107-3CT ± 4% accuracy of scale value)
- For left-hand tightening, use our torque wrenches with insert tool
- · Safe:
 - Haptic (close-gap release)
 - Audible ("click" sound)
- Designed for rough workshop use
- Wide range of applications for controlled screw tightening in tyre service, bicycle, passenger car and commercial vehicle applications as well as various applications in trade and industry
- Optimised sealing ring to protect against debris
- Ratchet repair set for customer-oriented self-assembly enables decades of use
- Handle with better grip for easier power transmission
- Adjustment aid with detent points for optimised operator guidance ensures safe and fast adjustment of the desired torque value by turning
 the handle
- Safe locking of the setting values by latching function on the rotary assembly
- Rotary assembly in triangular form prevents uncontrolled rolling
- · Lock symbols indicate the respective locking status
- Can be attached to the cable loop through openings on the locking rotary assembly
- Easy-to-read, high-contrast scale
- Permanent readability due to laser marking on the scale bush
- Integrated shift lever
 - 5121-3CT 5123-3CT: shift lever with idle function reduces risk of injury and malfunction
- With calibration certificate and serial number
- Delivery in sturdy Hexa plastic box
- DIN EN ISO 6789-2:2017, DIN 3120, ISO 1174-1
- Made in Germany
- Output: 10 %
- Dimensions / length: 375 mm
- Net weight: 0.8 kg
- For manual operation
- Torque range min-max: 20 120 Nm
- Accuracy: 3 %

Product data sheet 5111-3 CT EAN-No. 4000896235384



• Scale Graduation (Nm): 1 Nm

• Actuating force min.-max. kg: 6.9 - 43.5 kg

• Number of teeth: 30 (Opening angle 12°)

• Head Thickness a: 14.5 mm

• Head Width b: 32 mm

• No more turning back: Continuous long-term tests on the 5000 series and 6000 series of HAZET torque wrenches have demonstrated that turning them back to the smallest scale value is not required

SYSTEM 5000-3 CT workshop torque wrench \cdot 1 – 800 Nm \cdot with reversible ratchet \cdot accuracy \pm 3 / 4 %

Order Number 5111-3 CT