

Product data sheet

6108-1 CT CAL

EAN-No. 4000896192908



Length: 198 mm · Torque range min-max: 2 – 10 Nm · Accuracy: 2 % · $\frac{63}{8}$ 1/4 · Mit DAkkS-Kalibrierschein



- Torque wrench **with DAkkS calibration certificate**
- Safe:
 - Haptic (close-gap release)
 - Audible ("click" sound)
- Safe and fast adjustment of the desired torque value by turning the handle
- Especially slim design thanks to spring-loaded puller sleeve for locking the setting values
- **Accuracy $\pm 2\%$ of the scale value** (6106-1CT: $\pm 4\%$) (in direction of actuation for right-hand tightening)
For left-hand tightening, use our torque wrenches with insert tool
- Application: engines, gearboxes, machinery, industry, model making
- With calibration certificate and serial number
- DIN EN ISO 6789-2:2017, DIN 3120, ISO 1174-1
- Made in Germany
- Output: $\frac{63}{8}$ 1/4
- Dimensions / length: 198 mm
- For manual operation
- Torque range min-max: 2 – 10 Nm
- Accuracy: 2 %
- Scale Graduation (Nm): 0.2 Nm
- Actuating force min.-max. kg: 1.4 – 7.3 kg
- Number of teeth: 90 (Opening angle 4°)
- Head Thickness a: 10.2 mm
- Head Width b: 24 mm
- **No more turning back:** Continuous long-term tests on the 5000 series and 6000 series of HAZET torque wrenches have demonstrated that turning them back to the smallest scale value is not required

DAkkS calibration certificate for the professional user, especially for:

- Aviation industry
- Automobile industry
- New-energy, wind turbines, offshore wind farms
- Petrochemical industry (oil/gas)

Documented traceability guarantees complete verifiability

SYSTEM 6000-1 CT industrial torque wrench · 1 – 2000 Nm · with reversible ratchet · accuracy $\pm 2 / 4\%$

Order Number

6108-1 CT CAL