

# Product data sheet

**5121 KV** EAN-No. 4000896233397



Length: 420 mm · Torque range min-max: 20 – 120 Nm · Accuracy: 4 % ·  $\frac{1}{2}$ "



- **Can be calibrated**
- **Long service life / high accuracy**
- Option of:
  - Removal
  - Repair (if necessary)
  - Installation
  - Adjustment
  - Calibration
- **Note: adjustment, possible repairs with removal/installation of the KV torque wrench only in the HAZET Service Center**
- Suitable for control of inspection and test equipment
- Sustainable and environmentally sound
- Safety:
  - Haptic (close-gap release)
  - Audible (“click” sound)
- **Right/left release** by plug-in square, thereby tightening at torque setting, both to the right and to the left within the specified accuracy
- Low weight for good handling and fatigue-free work

#### Product design features

- Slim design in strict accordance with the required insulating properties (material strength/overlaps)
- Smooth transitions on switching and moving parts with ergonomic handle design and calibration notch
- Uniform look even when using other components (e.g. red insulated sockets)
- Attractive colour design of the housing and head with signal colours red/yellow
- Handle in black to make a distinction with the colour and to prevent it from quickly appearing dirty
- To prevent disturbing projecting parts (e.g. shift lever)

#### ATTENTION:

Repairs may only be carried out by the HAZET Service Center, as repair works must be followed by a 10,000 V routine test in accordance with IEC 60900

- DIN EN ISO 6789-2:2017, DIN 3120, ISO 1174-1, IEC 60900:2018
- Made in Germany
- Output:  $\frac{1}{2}$ "
- Dimensions / length: 420 mm
- 
- For manual operation

# Product data sheet

## 5121 KV

EAN-No. 4000896233397



- Torque range min-max: 20 – 120 Nm
- Accuracy: 4 %
- Scale Graduation (Nm): 1 Nm
- Actuating force min.-max. kg: 6.0 – 37.4 kg
- Number of teeth: 32 (Opening angle 11.25°)
- **No more turning back:** Continuous long-term tests on the 5000 series and 6000 series of HAZET torque wrenches have demonstrated that turning them back to the smallest scale value is not required

**Order Number**

5121 KV

**Protective insulation**

