

# Product data sheet

## 1979 W-82

EAN-No. 4000896227228



L x W x H: 133 mm x 65 mm x 23 mm



### Application:

Small design for use in areas with restricted access

#### • **Wireless charging**

- Efficient and comfortable charging function due to optimised self-positioning of the lamp on the pad
- 180° adjustable, 8-step lockable base for adjustment of work area illumination
- Progressively dimmable – optimal light adjustment
- Strong rubberised holding magnets on the underside and rear side of the housing
- 360° movable retaining hook

#### • **Main light:**

Operating time 2 – 10 h  
Luminous flux 30 – 300 lumen  
3-watt COB LED

#### • **Top light:**

Operating time top light: 5 h  
Luminous flux 100 lumen  
1-watt LED

- Charging starts immediately after the light is fitted
- 2-component plastic housing with rubberised surface
- 4-stage battery status and state-of-charge display
- Switching on / off as well as switching between top and main light via main button
- Number of batteries: 1 x 3.7 V 1200 mAh Lithium-ion rechargeable battery
- Power supply: Wireless charging
- LED technology: COB/SMD
- Luminous flux 100%: 300 lm
- Operating time 100%: 2 h
- Charging time: 1.5 h
- Type of protection (IP): IP65
- Protection rating (IK): IK09
- Dimensions / length: 133 mm x 65 mm x 23 mm

# Product data sheet

## 1979 W-82

EAN-No. 4000896227228



Order Number

1979 W-82