

Product data sheet

9012 ATT

EAN-No. 4000896234738



L x W x H: 85 mm x 64 mm x 227 mm · Loosening torque maximum [Nm]: 550 Nm · $\frac{1}{2}$ " · Abgewinkelt · Powerful twin hammer mechanism



Application:

Operating brake calliper screw connections as well as other hard-to-reach screw-joints

- Loosening torque maximum [Nm]: 550 Nm
- Exhaust air is guided through the handle downwards
- Reduced vibrations
- Easy handling
- Handle / trigger adjustable around its own axis for optimal handling allows operation in any position
- Swivel mechanism for extended application range guarantees best accessibility
- Short, compact, angled design – only 70 mm
- One-hand operation for left- and right-handed users
- Powerful twin hammer mechanism
- Air connection inlet: inside thread (IG) 12.91 mm (1/4")
- Coupler plug: Nominal size 7.2 (included)
- Recommended torque: 450 Nm
- Hose diameter (recommended): 10 mm
- Working pressure (bar): 6.3
- Sound power level: 101.1 db(A) L_p W
- Vibration acceleration: 4.89 m/s²
- Loosening torque (maximum) determined with screw size M: 16
- Forward and reverse: single-stage (right/left)
- Cold insulated handle
- Output: $\frac{1}{2}$ "
- Dimensions: 85 mm x 64 mm x 227 mm
- Net weight: 1.3 kg
- For impact operation
- Tightening torque maximum [Nm]: 500 Nm
- Loosening torque maximum [Nm]: 550 Nm

Product data sheet

9012 ATT

EAN-No. 4000896234738



- Sound pressure level: 90.1 dB(A) Lp A
- Revolutions per minute: 8000
- Air requirement: 113 l/min (1.9 l/sec)

Handle	Cold insulated handle
Order Number	9012 ATT