Product data sheet

4903-3 EAN-No. 4000896**179848**





- Increased safety thanks to load-free installation
- Universal tensioning jaw · adjustable
- · Can be used for almost any spring strut / shock absorber strut
- · Load-free disassembly / assembly with completely relieved shock absorber

Innovative socket and installation concept

- Swivels in horizontal or vertical working position,
 HAZET recommends ergonomic working height: adjust vertically, operate horizontally
- Damage to shock absorbers and head plates impossible (no overload risk)
- Simple, lockable strut mount

High safety

- · Consistently reliable mounting of head plates
- Thread damage to piston rod impossible
- Permanent fixation of spring throughout operation

Secured investment - by using existing components of SYSTEM 4900

- Existing basic units 4900-2A and all tensioning jaws of System 4900 may be used
- Use of future applications is assured

Allows record keeping by scaling

- If recurring, significant time savings by scaling
- Firm fixation eliminates readjustment at the same spring strut (left/right)

4 steps to success:

- 1. Fix spring strut on clamping disc via gripper and brakes
- 2. Grip spring with universal tensioning jaw
- 3. Operate tensioning device with reversible ratchet, cordless screwdriver or pneumatic air ratchet
- 4. Disassemble shock absorber without load and install new one (afterwards in reverse order)
- · Made in Germany
- Net weight: 18.1 kg

Order Number 4903-3