

# Product data sheet

## 9012 SPC

EAN-No. 4000896119639



Loosening torque maximum [Nm]: 850 Nm ·  $\frac{125}{16}$  1/2 · Powerful pin clutch mechanism



- Loosening torque maximum [Nm]: 850 Nm
- Higher power delivery as well as more efficient air flow and improved response torque of the air motors
- Especially heat-treated inner parts for minimised wear
- Exhaust air is guided through the handle downwards
- Reduced vibrations
- Easy handling
- Powerful pin clutch mechanism
- Air connection inlet: inside thread (IG) 12.91 mm (1/4" )
- Coupler plug: Nominal size 7.2 (included)
- Recommended torque: 550 Nm
- Hose diameter (recommended): 10 mm
- Working pressure (bar): 6.3
- Sound power level: 103.1 db(A) Lp W
- Vibration acceleration: 7.42 m/s<sup>2</sup>
- Loosening torque (maximum) determined with screw size M: 16
- Forward and reverse: three-stage (forward), single-stage (reverse)
- Cold insulated handle
- Output:  $\frac{125}{16}$  1/2
- Net weight: 2.6 kg
- For impact operation
- Tightening torque maximum [Nm]: 750 Nm
- Loosening torque maximum [Nm]: 850 Nm
- Sound pressure level: 92.1 dB(A) Lp A
- Revolutions per minute: 7000
- Air requirement: 127.4 l/min (2.1 l/sec)

# Product data sheet

## 9012 SPC

EAN-No. 4000896119639



**Handle**

Cold insulated handle

**Order Number**

9012 SPC