

# Product data sheet

## 6106-1 CT CAL

EAN-No. 4000896192892



Length: 197 mm · Torque range min-max: 1 – 6 Nm · Accuracy: 4 % ·  $\frac{63}{16}$  · Mit DAkkS-Kalibrierschein



- Torque wrench **with DAkkS calibration certificate**
- Safe:
  - Haptic (close-gap release)
  - Audible ("click" sound)
- Safe and fast adjustment of the desired torque value by turning the handle
- Especially slim design thanks to spring-loaded puller sleeve for locking the setting values
- **Accuracy  $\pm 2\%$  of the scale value** (6106-1CT:  $\pm 4\%$ ) (in direction of actuation for right-hand tightening)  
For left-hand tightening, use our torque wrenches with insert tool
- Application: engines, gearboxes, machinery, industry, model making
- With calibration certificate and serial number
- DIN EN ISO 6789-2:2017, DIN 3120, ISO 1174-1
- Made in Germany
- Output:  $\frac{63}{16}$
- Dimensions / length: 197 mm
- For manual operation
- Torque range min-max: 1 – 6 Nm
- Accuracy: 4 %
- Scale Graduation (Nm): 0.1 Nm
- Actuating force min.-max. kg: 0.7 – 4.4 kg
- Number of teeth: 90 (Opening angle 4°)
- Head Thickness a: 10.2 mm
- Head Width b: 24 mm
- **No more turning back:** Continuous long-term tests on the 5000 series and 6000 series of HAZET torque wrenches have demonstrated that turning them back to the smallest scale value is not required

**DAkkS calibration certificate** for the professional user, especially for:

- Aviation industry
- Automobile industry
- New-energy, wind turbines, offshore wind farms
- Petrochemical industry (oil/gas)

Documented traceability guarantees complete verifiability

SYSTEM 6000-1 CT industrial torque wrench · 1 – 2000 Nm · with reversible ratchet · accuracy  $\pm 2 / 4\%$

Order Number

6106-1 CT CAL