Length: 2455 mm · Torque range min-max: 600 – 1600 Nm · Accuracy: 3 % · ▣1

- For the highest torque values

1600 Nm torque wrench
Weight only about 14 kg

- Actuating force only 685 N (70 kg) at 1600 Nm
- Length of ratchet shaft 1316.5 mm, handle 1203 mm
- **Accuracy ± 3 % of the scale value** (6170-1CT: ± 4 %) (in direction of actuation for right-hand tightening)
  For left-hand tightening, use our torque wrenches with insert tool
- For industrial climbers
- Application on wind turbines, dockyards, in the aviation industry and heavy industry, on commercial vehicles etc.
- Dismountable in 2 parts (6170-1CT 3 parts) with release tool
- Bag included for safe storage and for carrying or wearing on your back
- Fast screw tightening also possible with ratchet shaft alone. For torque tightening always use the complete wrench
- Safety:
  – Haptic (close-gap release)
  – Audible ("click" sound)
- **2-component handle** for improved feel
- Simplified locking for adjusting the torque value
- Viewing window for visual checking of the locking
- 4 coloured coding rings (red, yellow, green, black) for markings in the case of personalisation or special workflows
- With calibration certificate and serial number
- DIN EN ISO 6789-2:2017, DIN 3120, ISO 1174-1
- Made in Germany
- Output: ▣1
- Dimensions / length: 2455 mm
- Net weight: 14 kg
- For manual operation
- Torque range min-max: 600 – 1600 Nm
- Accuracy: 3 %
- Scale Graduation (Nm): 5 Nm
- Actuating force min.-max. kg: 26.1 – 70.1 kg
- Number of teeth: 32 (Opening angle 11.25°)
- Head Thickness a: 36 mm
- Head Width b: 77 mm
- **No more turning back:** Continuous long-term tests on the 5000 series and 6000 series of HAZET torque wrenches have demonstrated that turning them back to the smallest scale value is not required

SYSTEM 6000-1 CT industrial torque wrench · 1 – 2000 Nm · with reversible ratchet · accuracy ± 2 / 4 %

Order Number	6160-1 CT