

Product data sheet

6291-2 CT EAN-No. 4000896026104



Length: 389 mm · Torque range min-max: 20 – 120 Nm · Accuracy: 2 % ·



- Plug connection for holding insert tools
- **Accuracy $\pm 2\%$ of the scale value** (in the direction of actuation)
Can be used for right-hand and left-hand threads by turning the insert tool
- Safe:
 - Haptic (close-gap release)
 - Audible ("click" sound)
- With calibration certificate and serial number
- Safe and fast adjustment of the desired torque value by turning the handle
- Secure storage in safe box with inspection window
- DIN EN ISO 6789-2:2017
- Made in Germany
- Output:
- Dimensions / length: 389 mm
- Net weight: 0.85 kg
- For manual operation
- Torque range min-max: 20 – 120 Nm
- Accuracy: 2 %
- Scale Graduation (Nm): 1 Nm
- Effective torque wrench length min.-max. l1 mm: 348.30 – 334.20 Nm
- Actuating force min.-max. kg: 5.9 – 36.6 kg
- Inside micrometre of the adjusting tool l2: 30 mm
- Head Thickness a: 18 mm
- Head Width b: 23 mm
- **No more turning back:** Continuous long-term tests on the 5000 series and 6000 series of HAZET torque wrenches have demonstrated that turning them back to the smallest scale value is not required

SYSTEM 6200-1 CT insert torque wrench · 2 – 500 Nm · with insert square · accuracy $\pm 2/4\%$

Order Number

6291-2 CT