

# Product data sheet

9012 M/4 EAN-No. 4000896202843



4-pieces · 17 · 19 · Loosening torque maximum [Nm]: 1100 Nm ·  $\frac{1}{2}$ " · Single hammer striking mechanism



- Loosening torque maximum [Nm]: 1100 Nm
- **Extremely compact construction enables working in areas with restricted access**
- One-hand operation for right and left handed operators
- Exhaust air is guided downwards through the handle
- Reduced vibrations
- Easy handling

#### Extra short – only 92 mm

- Single hammer striking mechanism
- Air connection inlet: inside thread (IG) 12.91 mm (1/4" )
- Coupler plug: Nominal size 7.2 (included)
- Recommended torque: 610 Nm
- Hose diameter (recommended): 10 mm
- Working pressure (bar): 6.3
- Sound power level: 108.1 db(A) Lp W
- Vibration acceleration: 9.57 m/s<sup>2</sup>
- Loosening torque (maximum) determined with screw size M: 16
- Forward and reverse: three-stage (forward), single-stage (reverse)
- Cold insulated handle
- Output:  $\frac{1}{2}$ "
- Net weight: 1.24 kg
- For impact operation
- Tightening torque maximum [Nm]: 678 Nm
- Loosening torque maximum [Nm]: 1100 Nm
- Sound pressure level: 97.1 dB(A) Lp A
- Revolutions per minute: 10000
- Air requirement: 127 l/min (2.1 l/sec)
- Number of tools: 4

# Product data sheet

## 9012 M/4

EAN-No. 4000896202843



### Handle

Cold insulated handle

Order Number

9012 M/4



197-3



903SLG • • 1/2  
17 • 19



9012M • 1/2