

Product data sheet

9012 M-1

EAN-No. 4000896218356



Length: 80 mm · Loosening torque maximum [Nm]: 1200 Nm · $\frac{1}{2}$ " · Single hammer striking mechanism



- Loosening torque maximum [Nm]: 1200 Nm
- **Extremely compact construction enables working in areas with restricted access**
- One-hand operation for right- and left-handed users
- Exhaust air is guided through the handle downwards
- Reduced vibrations
- Easy handling
- **Extra short – only 80 mm**
- Single hammer striking mechanism
- Air connection inlet: inside thread (IG) 12.91 mm (1/4")
- Coupler plug: Nominal size 7.2 (included)
- Recommended torque: 610 Nm
- Hose diameter (recommended): 10 mm
- Working pressure (bar): 6.3
- Sound power level: 103.2 db(A) Lp W
- Vibration acceleration: 13.49 m/s²
- Loosening torque (maximum) determined with screw size M: 16
- Forward and reverse: three-stage (forward), single-stage (reverse)
- Cold insulated handle
- Output: $\frac{1}{2}$ "
- Dimensions: 80 mm
- Net weight: 1.27 kg
- For impact operation
- Tightening torque maximum [Nm]: 678 Nm
- Loosening torque maximum [Nm]: 1200 Nm
- Sound pressure level: 92.2 dB(A) Lp A
- Revolutions per minute: 8800
- Air requirement: 127.4 l/min (2.1 l/sec)

Product data sheet

9012 M-1

EAN-No. 4000896218356



Handle

Cold insulated handle

Order Number

9012 M-1