

# Product data sheet

**1979 W-92** EAN-No. 4000896**241422**



**L x W x H: 367 mm x 62 mm x 47 mm**



- **Wireless charging**
- Efficient and comfortable charging function due to optimised self-positioning of the lamp on the pad
- Charging starts immediately after the light is fitted
- Wireless charging pad 1979WP-1 or 1979WP-2 is needed
- 2-component plastic housing with rubberised surface
- 4-stage battery status and state-of-charge display
- 120° adjustable, 5-step lockable aluminium head for adjustment of work area illumination
- Battery capacity: 4500 mAh (milliampere hours) (+30 % compared to previous model)
- Main light operating time: approx. 3 – 14 h
- Top light operating time: 11 h
- Main light luminous flux: 110 – 1100 lumen (+10 % compared to predecessor)
- Top light luminous flux: 150 lumen
- Full-surface, homogenous illumination
- Dimmer switch on the rear side of the lamp – optimal light adjustment
- Switching between top and main light using the main button
- Strong rubberised holding magnet on the underside
- Fold-out and 360° rotatable hanging hook
- Solid base for good stability even on non-metallic substrates
- Number of batteries: 1 x 3.6 V 4500 mAh lithium-ion rechargeable battery
- Power supply: Wireless charging
- LED technology: COB/SMD
- Luminous flux 100%: 1100 lm
- Operating time 100%: 3 h
- Charging time: 5.5 h
- Type of protection (IP): IP65
- Protection rating (IK): IK08
- Dimensions / length: 367 mm x 62 mm x 47 mm

# Product data sheet

## 1979 W-92

EAN-No. 4000896241422



Order Number

1979 W-92