

Product data sheet

9033 M-7 EAN-No. 4000896227242



Length: 129 mm



Application:

Handy and light tool for working in areas with difficult access

- Heavy-duty multi-bearing gearbox with a 2.5-times longer service life compared to conventional gearboxes
- For grinding wheels: 50 – 59 mm
- For grinding wheel thickness: 1 – 4 mm
- Adjustable protective cover
- Spindle thread: $\frac{3}{8}$ " 24 UNF
- Exhaust air is guided through the handle
- Air connection inlet: inside thread (IG) 12.91 mm ($\frac{1}{4}$ ")
- Coupler plug: Nominal size 7.2 (included)
- Hose diameter (recommended): 10 mm
- Working pressure (bar): 6.3
- Sound power level: 96.8 db(A) Lp W
- Vibration acceleration: 1.90 m/s²
- Power in watts: 224 Watt
- Cold insulated handle
- Dimensions: 129 mm
- Net weight: 0.53 kg
- Sound pressure level: 85.8 dB(A) Lp A
- Revolutions per minute: 18000
- Air requirement: 84 l/min (1.4 l/sec)

"Mini" pneumatic tools range

- Innovative 5-slat concept for even more power than conventional drives
- High reliability and continuous operation

Handle	Cold insulated handle
Order Number	9033 M-7