

# Product data sheet

**1979 W-85** EAN-No. 4000896**241484**



**L x W x H: 255 mm x 55 mm x 35 mm**



- **Wireless charging**
- Efficient and comfortable charging function due to optimised self-positioning of the lamp on the pad
- Charging starts immediately after the light is fitted
- Wireless charging pad 1979WP-1 or 1979WP-2 is needed
- Battery status and state-of-charge display
- Main light operating time: approx. 3 – 20 h
- Top light operating time: 4.5 h
- Main light luminous flux: 60 – 600 lumen
- Top light luminous flux: 300 lumen
- Dimmer switch for optimal light adjustment. Switching between top and main light
- Dimmer switch on the rear side of the lamp – optimal light adjustment
- Strong rubberised holding magnet on the underside
- Fold-out and 360° rotatable hanging hook
- 180° adjustable and 5-stage lockable foot
- Number of batteries: 1 x 3.7 V 2600 mAh Lithium-ion rechargeable battery
- Power supply: Wireless charging
- LED technology: COB/SMD
- Luminous flux 100%: 600 lm
- Operating time 100%: 3 h
- Charging time: 3.5 h
- Type of protection (IP): IP65
- Protection rating (IK): IK09
- Dimensions / length: 255 mm x 55 mm x 35 mm

**Order Number**

1979 W-85