

Product data sheet

9013 M/6

EAN-No. 4000896229420



6-pieces · 17 · 19 · Loosening torque maximum [Nm]: 1890 Nm · $20 \frac{3}{4}$ · Powerful twin hammer mechanism



- Loosening torque maximum [Nm]: 1890 Nm
- Exhaust air is guided through the handle downwards
- Reduced vibrations
- Easy handling
- Powerful twin hammer mechanism
- Air connection inlet: inside thread (IG) 16.41 mm (3/8")
- Coupler plug: Nominal size 7.2 (included)
- Recommended torque: 922 Nm
- Hose diameter (recommended): 10 mm
- Working pressure (bar): 6.3
- Sound power level: 93 db(A) Lp W
- Vibration acceleration: 7.47 m/s²
- Loosening torque (maximum) determined with screw size M: 32
- Forward and reverse: three-stage (forward), single-stage (reverse)
- Cold insulated handle
- Output: $20 \frac{3}{4}$
- For impact operation
- Tightening torque maximum [Nm]: 1085 Nm
- Loosening torque maximum [Nm]: 1890 Nm
- Sound pressure level: 104 dB(A) Lp A
- Revolutions per minute: 7300
- Air requirement: 153 l/min (2.5 l/sec)
- Number of tools: 6



Handle	Cold insulated handle
Order Number	9013 M/6


Product data sheet

9013 M/6



EAN-No. 4000896229420



903SLG6 •  •  17½,
17 • 19

1000S-Z •  ¾
1000S-G1736 • 1000S-
H1736



1003S-1 •  •  ¾