

Product data sheet

6128-1 CT

EAN-No. 4000896076116



Length: 660 mm · Torque range min-max: 67.8 – 339 Nm · lbf min-max: 50 – 250 lbf.ft · Accuracy: 3 % · $\frac{1}{2}$ "



- According to US standards
 - Scale graduation in lbf.ft
 - Accuracy $\pm 3\%$ of the scale value (in direction of actuation for right-hand tightening)
For left-hand tightening, use our torque wrenches with insert tool
 - Safe:
 - Haptic (close-gap release)
 - Audible ("click" sound)
 - Safe and fast adjustment of the desired torque value by turning the handle
 - HiPer fine-tooth reversible ratchet in 6127-1CT (90 teeth · 4° operating angle)
 - Knob for additionally locking the set value
 - Secure storage in safe box with display window
 - With calibration certificate and serial number
 - DIN EN ISO 6789-2:2017, DIN 3120, ISO 1174-1
 - Made in Germany
 - Output: $\frac{1}{2}$ "
 - Dimensions / length: 660 mm
 - Net weight: 1.65 kg
 - For manual operation
 - Torque range min-max: 67.8 – 339 Nm
 - lbf min-max: 50 – 250 lbf.ft
 - Accuracy: 3 %
 - Scale Graduation (lbf.ft): 2 lbf.ft
 - Effective torque wrench length min.-max. l1 mm: 565.98 – 551.88 Nm
 - Actuating force min.-max. kg: 12.2 – 62.6 kg
 - Number of teeth: 90 (Opening angle 4°)
 - Head Thickness a: 19.6 mm
 - Head Width b: 44 mm
 - **No more turning back:** Continuous long-term tests on the 5000 series and 6000 series of HAZET torque wrenches have demonstrated that turning them back to the smallest scale value is not required
- SYSTEM 6000-1 CT US torque wrench · 5 – 600 lbf.ft · US standard · with reversible ratchet · accuracy $\pm 3\%$

Order Number

6128-1 CT