Product data sheet
6391-85 EAN-No. 4000896027071

Length: 316 mm · Torque range min-max: 15 – 85 Nm · Accuracy: 2 % · 9 x 12

- **Accuracy ± 2% (6391-10: 6%) of the preset value** (in direction of actuation)
  Can be used for right-hand and left-hand threads by turning the insert tool
- Plug connection, for holding insert tools
- **Permanently adjustable value**
- Especially suitable for application in industrial series fabrication
- Adjusting the desired torque value with adjustment wrench 6399 in conjunction with HAZET torque tester 7901E · 7902E · 7903E or another suitable device
- **All wrenches of this series (HAZET 6391-6392) are without an adjusting scale**
- With calibration certificate and serial number
- DIN EN ISO 6789-2:2017
- Made in Germany
- Output: 9 x 12
- Dimensions / length: 316 mm
- Net weight: 0.34 kg
- For manual operation
- Torque range min-max: 15 – 85 Nm
- Accuracy: 2 %
- Effective torque wrench length min.-max. l1 mm: 306.00 – 306.00 Nm
- Actuating force min.-max. kg: 5.0 – 28.3 kg
- Inside micrometre of the adjusting tool l2: 30 mm
- Head Thickness a: 17 mm
- Head Width b: 22 mm

SYSTEM 6300 CT industrial insert torque wrench · 2 – 320 Nm · with insert square · fixed adjustable value · accuracy ± 2 %

Order Number	6391-85