

Product data sheet

6114-1 CT

EAN-No. 4000896078424



Length: 333 mm · Torque range min-max: 6.8 – 54.2 Nm · lbf min-max: 5 – 40 lbf.ft · Accuracy: 3 % · ± 10 %



- **According to US standards**
- Scale graduation in **lbf.ft**
- **Accuracy ± 3 % of the scale value** (in direction of actuation for right-hand tightening)
For left-hand tightening, use our torque wrenches with insert tool
- Safe:
 - Haptic (close-gap release)
 - Audible ("click" sound)
- Safe and fast adjustment of the desired torque value by turning the handle
- **HiPer fine-tooth reversible ratchet** in 6127-1CT (90 teeth · 4° operating angle)
- Knob for additionally locking the set value
- Secure storage in safe box with display window
- With calibration certificate and serial number
- DIN EN ISO 6789-2:2017, DIN 3120, ISO 1174-1
- Made in Germany
- Output: ± 10 %
- Dimensions / length: 333 mm
- Net weight: 0.56 kg
- For manual operation
- Torque range min-max: 6.8 – 54.2 Nm
- lbf min-max: 5 – 40 lbf.ft
- Accuracy: 3 %
- Scale Graduation (lbf.ft): 0.5 lbf.ft
- Effective torque wrench length min.-max. l1 mm: 264.52 – 254.02 Nm
- Actuating force min.-max. kg: 2.6 – 21.8 kg
- Number of teeth: 90 (Opening angle 4°)
- Head Thickness a: 14.5 mm
- Head Width b: 32 mm
- **No more turning back:** Continuous long-term tests on the 5000 series and 6000 series of HAZET torque wrenches have demonstrated that turning them back to the smallest scale value is not required

SYSTEM 6000-1 CT US torque wrench · 5 – 600 lbf.ft · US standard · with reversible ratchet · accuracy ± 3 %

Order Number

6114-1 CT