

# Product data sheet

## 9022-360

EAN-No. 4000896209781



Length: 285 mm ·  $\frac{1}{2}$ "



### Application:

Operation of screw connections in confined spaces

- 360° rotatable operating lever
- 30% less noise thanks to the ability to reduce operating noise / Quiet Mode (approx. 10 dB)
- Flat head without an interfering edge thanks to the shift lever
- Switching between left and right via the adjusting ring on the handle
- Head made of heat-treated special steel
- **Long service life (tool availability)** and equipment load capacity
- Quiet Mode:
  - Sound power level: 92.5 db(A) Lp W
  - Sound pressure level: 81.5 db(A) Lp A
- For manual retightening with torque values: 500 Nm (competing products: approx. 250 Nm)
- Air connection inlet: inside thread (IG) 12.91 mm (1/4" )
- Coupler plug: Nominal size 7.2 (included)
- Hose diameter (recommended): 10 mm
- Working pressure (bar): 6.3
- Sound power level: 102.2 db(A) Lp W
- Vibration acceleration: 4.87 m/s<sup>2</sup>
- Forward and reverse: single-stage (right/left)
- Cold insulated handle
- Output:  $\frac{1}{2}$ "
- Dimensions: 285 mm
- Net weight: 1.55 kg
- For impact operation
- Tightening torque maximum [Nm]: 120 Nm
- Sound pressure level: 91.2 dB(A) Lp A
- Revolutions per minute: 200
- Air requirement: 107.6 l/min (1.8 l/sec)

<b>Handle</b>	Cold insulated handle
<b>Order Number</b>	9022-360