Product data sheet 9212-1000 LB/4 EAN-No. 4000896249909



4-pieces · Loosening torque maximum [Nm]: 1400 Nm · 2 1/2 · L-Boxx



Application:

Work independently

- High efficiency thanks to brushless motor
- 4-piece set · in HAZET L-Boxx 136 and soft foam insert:
 - 1 cordless impact wrench
 - 1 quick charger
 - 2 Li-ion batteries 18 V · 5 Ah (Ampere hours)
- 18 V · 5 Ah (Ampere hours)
- Suitable for continuous operation
- Robust machine housing
- There are three power stages to choose from for torque acceleration:
 - Stage 1 180 Nm at 0 400 rpm (0 800 impacts/min)
 - Stage 2 400 Nm at 0 800 rpm (0 1600 impacts/min)
 - Stage 3 1000 Nm at 0 1800 rpm (0 2200 impacts/min)
- · Illumination of the work area before the output begins to move
- Compatible with HAZET rechargeable batteries 9212-02 and 9212-05
- Dimensions including rechargeable battery: 278 x 230 x 89.5 mm
- Including belt clip, attachable on both sides
- Brushless DC motor (BLDC)
 - Longer service life, less wear, no need to change the carbon brushes
 - High efficiency and hence less battery consumption
 - More compact motor enables smaller installation dimensions
- Sound power level: 112 db(A) Lp W
- Vibration acceleration: 17.80 m/s2
- Loosening torque (maximum) determined with screw size M: 24
- Forward and reverse: multi-stage (right/left)
- L-Boxx 190 L-136
- Output: 125 1/2
- Net weight: 3.64 kg
- Tightening torque maximum [Nm]: 1000 Nm

Product data sheet 9212-1000 LB/4 EAN-No. 4000896249909



• Loosening torque maximum [Nm]: 1400 Nm

• Sound pressure level: 101 dB(A) Lp A

• Revolutions per minute: 0 – 1800

Do you know - Li-Ion batteries:

- Do not have any memory effect
- Consist of cells with 3.6 V each
- After full charge they have a higher voltage than 3.6 V i.e. 5 cells each 3.6 V = 18 V **but** after full charge a peak voltage of up to 20 V is possible

Attention: For a longer lifetime of the battery please store it charged up to 50 to 80 % only

- Have an energy density which is twice as high as nickel cadmium batteries, for example
- Have a nominal voltage three times higher than a nickel metal hydride battery
- Require multiple complete charging cycles to reach full capacity
- Number of tools: 4

Order Number 9212-1000 LB/4



9212-1000 • 125 1/2



9212-03



9212-05