

Product data sheet

9014 LGTT

EAN-No. 4000896234677



L x W x H: 424 mm x 133 mm x 307 mm · Loosening torque maximum [Nm]: 3850 Nm · 25 1' · Powerful twin hammer mechanism



Application:

Long service life and high efficiency in industrial and automotive applications

- Loosening torque maximum [Nm]: 3850 Nm
- Exhaust air is guided through the handle downwards
- Reduced vibrations
- Easy handling
- Short, compact design with 240 mm long spindle
- One-hand operation for left- and right-handed users
- Removable handle, 360° adjustable
- Connecting socket for low noise hose
- HAZET Twin Turbo technology – high torques with compact design
- 8-blade air motor with 25% higher impact performance ensures maximum torque
- Powerful twin hammer mechanism
- Air connection inlet: inside thread (IG) 20.67 mm (1/2")
- Coupler plug: nominal size 10 (included)
- Recommended torque: 1627 Nm
- Hose diameter (recommended): 19 mm
- Working pressure (bar): 6.3
- Sound power level: 113.5 db(A) Lp W
- Vibration acceleration: 17.31 m/s²
- Loosening torque (maximum) determined with screw size M: 32
- Forward and reverse: two-stage (forward), single-stage (reverse)
- Cold insulated handle
- Output: 25 1'
- Dimensions: 424 mm x 133 mm x 307 mm
- Net weight: 5.9 kg
- For impact operation
- Tightening torque maximum [Nm]: 1762 Nm
- Loosening torque maximum [Nm]: 3850 Nm

Product data sheet

9014 LGTT

EAN-No. 4000896234677



- Sound pressure level: 102.5 dB(A) Lp A
- Revolutions per minute: 4600
- Air requirement: 235 l/min (3.9 l/sec)

Handle	Cold insulated handle
Order Number	9014 LGTT