

Product data sheet


5107 B-3 CT

EAN-No. 4000896244584



Length: 234 mm · Torque range min-max: 1 – 9 Nm · Accuracy: 4 % · 



- User-friendly reversible ratchet for bits
- **Accuracy $\pm 3\%$ (5108B-3CT) or 4% (5107B-3CT) of the scale value** (in direction of actuation for right-hand tightening)
- Safety:
 - Haptic (close-gap release)
 - Audible (“click” sound)
- Designed for rough workshop use
- Wide range of applications for controlled screw tightening for bicycle, passenger car and commercial vehicle applications as well as various applications in trade and industry
- Optimised sealing ring to protect against debris
- Handle with better grip for easier power transmission
- Adjustment aid with detent points for optimised operator guidance ensures safe and fast adjustment of the desired torque value by turning the handle
- Safe locking of the setting values by latching function on the rotary assembly
- Rotary assembly in triangular form prevents uncontrolled rolling
- Lock symbols indicate the respective locking status
- Can be attached to the cable loop through openings on the locking rotary assembly
- Easy-to-read, high-contrast scale
- Permanent readability due to laser marking on the scale bush
- Integrated shift lever
- With calibration certificate and serial number
- Delivery in sturdy Hexa plastic box
- For e.g. maintenance and service work on the burner flange or the electrodes on compact modules for condensing and combi gas boilers
- For aluminium and carbon parts · plastic attached parts · fairings of motorcycles · scooters · bicycles
- DIN EN ISO 6789-2:2017
- Made in Germany
- Output: 
- Dimensions / length: 234 mm
- For manual operation
- Torque range min-max: 1 – 9 Nm
- Accuracy: 4 %
- Scale Graduation (Nm): 0.1 Nm
- Actuating force min.-max. kg: 0.6 – 5.5 kg
- Number of teeth: 20 (Opening angle 18°)
- Head Thickness a: 10.2 mm

Product data sheet

5107 B-3 CT

EAN-No. 4000896244584



- Head Width b: 24 mm
- **No more turning back:** Continuous long-term tests on the 5000 series and 6000 series of HAZET torque wrenches have demonstrated that turning them back to the smallest scale value is not required

SYSTEM 5000 B-3 CT workshop torque wrench · 1 – 25 Nm · with reversible ratchet for bits · accuracy $\pm 3 / 4 \%$

Order Number

5107 B-3 CT