

# Product data sheet

## 9023 M-1

EAN-No. 4000896227112



4-pieces ·  $\frac{6.3}{16}$  1/4",  $\frac{10}{16}$  3/8",  $\frac{6.3}{16}$  1/4"



### Application:

With the open 17 mm inside hexagon it is also possible to work on extra long threads

- Can be used for  $\frac{6.3}{16}$  1/4",  $\frac{10}{16}$  3/8" and  $\frac{6.3}{16}$  1/4" by replacing the ratchet heads

### Contents:

- Push-through ratchet
- Square socket 1/4" (6.3 mm)
- Square socket 3/8 (10 mm)
- Hexagon screwdriver bit socket 1/4" (6.3 mm)

- Short design
- Reduced vibrations
- Exhaust air is guided through the handle
- For manual retightening with torque values 70 Nm
- Air connection inlet: inside thread (IG) 12.91 mm (1/4" )
- Coupler plug: Nominal size 7.2 (included)
- Hose diameter (recommended): 10 mm
- Working pressure (bar): 6.3
- Sound power level: 93.8 db(A) Lp W
- Vibration acceleration: 3.20 m/s<sup>2</sup>
- Forward and reverse: single-stage (right/left)
- Cold insulated handle
- Output:  $\frac{6.3}{16}$  1/4",  $\frac{10}{16}$  3/8",  $\frac{6.3}{16}$  1/4"
- Dimensions / length: 159 mm
- Net weight: 0.48 kg
- For impact operation
- Tightening torque max Nm: 54 Nm
- Sound pressure level: 82.8 dB(A) Lp A
- Revolutions per minute: 400
- Air requirement: 84 l/min (1.4 l/sec)

### "Mini" pneumatic tools range

- Innovative 5-slat concept for even more power than conventional drives
- High reliability and continuous operation
- Number of tools: 4


<b>Handle</b>	Cold insulated handle
<b>Order Number</b>	9023 M-1

# Product data sheet


## 9023 M-1

EAN-No. 4000896227112




9023M-1-020 •  6.3 1/4"



9023M-1-021 •  10 3/8"



9023M-1-B •  8 1/4"