

# Product data sheet


## 5280-3 CT

EAN-No. 4000896239290



Length: 218 mm · Torque range min-max: 2.5 – 25 Nm · Accuracy: 3 % · 



- Plug connection for holding insert tools
- **Accuracy  $\pm 3\%$  of the scale value** (in the direction of actuation)  
Can be used for right-hand and left-hand threads by turning the insert tool
- Safe:
  - Haptic (close-gap release)
  - Audible ("click" sound)
- Designed for rough workshop use
- Wide range of applications for controlled screw tightening in tyre service, bicycle, passenger car and commercial vehicle applications as well as various applications in trade and industry
- Optimised sealing ring to protect against debris
- Handle with better grip for easier power transmission
- Adjustment aid with detent points for optimised operator guidance ensures safe and fast adjustment of the desired torque value by turning the handle
- Safe locking of the setting values by latching function on the rotary assembly
- Rotary assembly in triangular form prevents uncontrolled rolling
- Lock symbols indicate the respective locking status
- Can be attached to the cable loop through openings on the locking rotary assembly
- Easy-to-read, high-contrast scale
- Permanent readability due to laser marking on the scale bush
- With calibration certificate and serial number
- Delivery in sturdy Hexa plastic box
- DIN EN ISO 6789-2:2017
- Made in Germany
- Output: 
- Dimensions / length: 218 mm
- Net weight: 0.29 kg
- For manual operation
- Torque range min-max: 2.5 – 25 Nm
- Accuracy: 3 %
- Scale Graduation (Nm): 0.25 Nm
- Effective torque wrench length min.-max. l1 mm: 178.80 – 191.50 Nm
- Actuating force min.-max. kg: 1.3 – 14.3 kg
- Inside micrometre of the adjusting tool l2: 19.5 mm
- Head Thickness a: 17 mm
- Head Width b: 22 mm

# Product data sheet

## 5280-3 CT

EAN-No. 4000896239290



- **No more turning back:** Continuous long-term tests on the 5000 series and 6000 series of HAZET torque wrenches have demonstrated that turning them back to the smallest scale value is not required

SYSTEM 5200-3 CT insert torque wrench · 2.5 – 200 Nm · with insert square · accuracy  $\pm 3\%$

Order Number

5280-3 CT