## Product data sheet 9037 N-2 EAN-No. 4000896205578



## Length: 296.6 mm



- Pneumatic / hydraulic
  Suitable for stainless steel rivets up to 6.4 mm
- · Professional riveting, suitable for continuous operation with rivets of up to 6.4 mm made of steel, stainless steel, aluminium and copper
- Possible rivet sizes: 3.0  $\cdot$  3.2  $\cdot$  4.0  $\cdot$  4.8  $\cdot$  5.0  $\cdot$  6.0 and 6.4 mm
- 5 nose pieces (one pre-installed)
- Thread size of nose pieces: M10 x 1.25
- Total stroke: 15.8 mm
- High tractive power: 14700 N
- Particularly low noise level
- · Rotary joint for flexible use
- Rivet and nose piece template on the underside of the rivet gun
- Storage of the different nose pieces on the underside of the rivet gun
- Easy oil top ups using special design of the rivet gun
- Includes maintenance set for oil control (oil-supported pressure build-up)
- Air requirement: 2.64 I / stroke
- Air connection inlet: inside thread (IG) 12.91 mm (1/4" )
- Coupler plug: Nominal size 7.2 (included)
- Hose diameter (recommended): 10 mm
- Working pressure (bar): 6.3
- Cold insulated handle
- Dimensions: 296.6 mm
- Net weight: 2.11 kg

| Handle | Cold insulated handle |
|--------|-----------------------|
|        |                       |

Order Number 9037 N-2