

Product data sheet

9037 N-2 EAN-No. 4000896205578



Length: 296.6 mm



- Pneumatic / hydraulic
Suitable for stainless steel rivets up to 6.4 mm
- Professional riveting, suitable for continuous operation with rivets of up to 6.4 mm made of steel, stainless steel, aluminium and copper
- Possible rivet sizes: 3.0 · 3.2 · 4.0 · 4.8 · 5.0 · 6.0 and 6.4 mm
- 5 nose pieces (one pre-installed)
- Thread size of nose pieces: M10 x 1.25
- Total stroke: 15.8 mm
- High tractive power: 14700 N
- Particularly low noise level
- Rotary joint for flexible use
- Rivet and nose piece template on the underside of the rivet gun
- Storage of the different nose pieces on the underside of the rivet gun
- Easy oil top ups using special design of the rivet gun
- Includes maintenance set for oil control (oil-supported pressure build-up)
- Air requirement: 2.64 l / stroke
- Air connection inlet: inside thread (IG) 12.91 mm (1/4")
- Coupler plug: Nominal size 7.2 (included)
- Hose diameter (recommended): 10 mm
- Working pressure (bar): 6.3
- Cold insulated handle
- Dimensions / length: 296.6 mm
- Net weight: 2.11 kg

Handle	Cold insulated handle
Order Number	9037 N-2