

Product data sheet

7901 E

EAN-No. 4000896140671



L x W x H: 138 mm x 110 mm x 117 mm · Torque range min-max: 10 – 350 Nm · $\frac{1}{2}$ "



Application:

Simple and quick checking of torque wrenches


- Simple, intuitive operation
- Giant display with 17 mm large digits
- Traffic light function for evaluation of the measured value PLUS audible signal
- Calibrated measuring range in the clockwise direction of rotation
- Fixed inside square socket · $\frac{1}{2}$ " (12.5 mm)
- Switchable torque display in Nm · dNm · kgfm · kgfcm · lbf.ft · lbf.in · ft.lb · in.lb
- Configurable selection of desired units
- Fixing material (not included in the scope of delivery): hexagon socket screws ISO 4762 – M10 – 12.9
- Gross weight including plastic case and accessories approx. 3.9 kg
- Easy entry of up to 15 different target values and the respective permissible accuracy in the range of $\pm 1\%$ to $\pm 15\%$
- Accuracy $\pm 1\%$ (maximum display deviation)
- Digital readouts · 3 measurement procedures
 - Automatic click point detection (first peak · click)
 - Peak value measurement (final peak · dial)
 - Tracking measurement / display value (track)
- Triple signaling of measurement result:
 - Digital display in 17 mm font size
 - Traffic light function for assessing the torque value (yellow = too low · green = OK · red = too high)
 - Audible signal
- Robust aluminium housing for workshop use, surface powder-coated
- Large, high-contrast, luminous, easy-to-read LCD screen with backlighting
- Autonomous operation possible via powerbank (5 V · 1 Ampere)
- Maximum power consumption: 0.5 Wh · Energy efficiency rating 6
- Rapid test function with auto reset, without target value and accuracy specification, without evaluation
- Compatible with HAZET test software torque testing 7901E-D, micro USB socket for power supply and data transmission
- Protection rating IP 40, splash-proof display and membrane keyboard
- 10 adjustable menu languages: German · English · French · Spanish · Italian · Danish · Finnish · Swedish · Norwegian · Portuguese

Product data sheet

7901 E

EAN-No. 4000896140671



- Included in delivery:
 - USB power supply 90–264 V AC at 47–63 Hz output voltage: 5 V · 1 Ampere · USB 2.0 A socket including power plug adapters for EU · UK · USA · AUS
 - Cable (2 m) USB 2.0 A plug – USB 2.0 micro B plug
 - Calibration certificate and quick reference guide (detailed operating instructions online for download)
 - Stable mounting on work bench
- Drive:  1/2
- Dimensions / length: 138 mm x 110 mm x 117 mm
- Net weight: 2.15 kg

Current software on this item can be found at hazet.de → Software & spare parts → Downloads

Order Number

7901 E