

# Product data sheet

## 5123-2 CLT CAL

EAN-No. 4000896243266



Length: 660 mm · Torque range min-max: 60 – 320 Nm · Accuracy: 4 % ·  $\frac{125}{2}$  · Mit DAkkS-Kalibrierschein



- Click-Lens-Type with large display in the inspection window guarantees security for the user
- Torque wrench **with DAkkS calibration certificate**
- **Accuracy  $\pm 4\%$  of the scale value** (in direction of actuation for right-hand tightening)  
For left-hand tightening, use our torque wrenches with insert tool
- Safe:
  - Haptic (close-gap release)
  - Audible ("click" sound)
- Reversible ratchet
- Safe and fast adjustment of the desired torque value by turning the handle
- Knob for additionally locking the set value
- Three large digits for an easy-to-read torque setting
- With calibration certificate and serial number
- Secure storage in safe box with inspection window
- Surface: hard chrome plated
- DIN EN ISO 6789-2:2017, DIN 3120, ISO 1174-1
- Made in Germany
- Output:  $\frac{125}{2}$
- Dimensions / length: 660 mm
- For manual operation
- Torque range min-max: 60 – 320 Nm
- Accuracy: 4 %
- Scale Graduation (Nm): 2 Nm
- Actuating force min.-max. kg: 10.8 – 59.4 kg
- Number of teeth: 32 (Opening angle 11.25°)
- Head Thickness a: 19.6 mm
- Head Width b: 44 mm
- **Service-friendly** (do-it-yourself repair sets for ratchets)
- No risk of losing the square like there is with the wrench
- **Hard chrome-plated** steel tube - **slim**, but very sturdy and wear-resistant
- Integrated shift lever with free-running function on  $\frac{125}{2}$  model **reducing the risk of injury and malfunction**
- Ergonomically shaped handle with collar **reduces the risk of slipping-off and injury**
- Safety locking of the handle – no risk of injury!
- Safe and exact adjustment of the desired release torque.  
Optimal and easy reading of the torque value
- Large convex display (replaceable) optimises the readability
- **No more turning back:** Continuous long-term tests on the 5000 series and 6000 series of HAZET torque wrenches have demonstrated that turning them back to the smallest scale value is not required

**DAkkS calibration certificate** for the professional user, especially for:

# Product data sheet

## 5123-2 CLT CAL

EAN-No. 4000896243266



- Aviation industry
- Automobile industry
- New-energy, wind turbines, offshore wind farms
- Petrochemical industry (oil/gas)

Documented traceability guarantees complete verifiability

SYSTEM 5000 CLT torque wrench · 20 – 320 Nm · with display and reversible ratchet · accuracy  $\pm 4\%$

**Order Number**

5123-2 CLT CAL