

Product data sheet

6281-2 CT

EAN-No. 4000896183326



Length: 125.4 mm · Torque range min-max: 5 – 13 Nm · Accuracy: 4 % ·



Application:

Regulation of the control valve at the gas tank of **VW Up!** and **Caddy** model years 2012 → (adjustment is necessary after installation or removal)

- Extra short construction for areas with restricted access
- Plug connection for holding insert tools
- **Accuracy $\pm 4\%$ of the scale value** (in the direction of actuation)
Can be used for right-hand and left-hand threads by turning the insert tool
- Safe:
 - Haptic (close-gap release)
 - Audible ("click" sound)
- With calibration certificate and serial number
- Safe and fast adjustment of the desired torque value by turning the handle
- Surface: hard chrome plated
- DIN EN ISO 6789-2:2017
- Made in Germany
- Output:
- Dimensions / length: 125.4 mm
- Net weight: 0.23 kg
- For manual operation
- Torque range min-max: 5 – 13 Nm
- Accuracy: 4 %
- Scale Graduation (Nm): 0.2 Nm
- Effective torque wrench length min.-max. l1 mm: 116.50 – 112.50 Nm
- Actuating force min.-max. kg: 4.4 – 11.8 kg
- Inside micrometre of the adjusting tool l2: 17.5 mm
- Head Thickness a: 17 mm
- Head Width b: 22 mm
- **No more turning back:** Continuous long-term tests on the 5000 series and 6000 series of HAZET torque wrenches have demonstrated that turning them back to the smallest scale value is not required

SYSTEM 6200-1 CT insert torque wrench · 2 – 500 Nm · with insert square · accuracy $\pm 2/4\%$

Order Number

6281-2 CT