

Product data sheet

1979 N-82

EAN-No. 4000896227211



L x W x H: 133 mm x 65 mm x 23 mm



Application:

Small design for use in areas with restricted access

- 180° adjustable, 8-step lockable base for adjustment of work area illumination
- 2-component plastic housing with rubberised surface
- Progressively dimmable – optimal light adjustment
- 4-stage battery status and state-of-charge display
- Switching on / off as well as switching between top and main light using the main button
- Strong rubberised holding magnet on the underside
- 360° movable retaining hook
- Impact resistance (EN62262): IK09
- **Main light:**
 - Operating time: 2 – 10 h
 - luminous flux 30 – 300 Lumen
 - 3 Watt COB LED
- **Top light:**
 - Operating time: 5 h
 - Luminous flux: 100 lumen
- 1x USB-C cable, 100 cm · without USB power supply unit
- Charging option using the standard USB power supply unit 5 V maximum 1 Ampere
- Number of batteries: 1 x 3.7 V 1200 mAh Lithium-ion rechargeable battery
- Power supply: USB cable (USB C)
- LED technology: COB/SMD
- Luminous flux 100%: 300 lm
- Operating time 100%: 2 h
- Charging time: 1.5 h
- Type of protection (IP): IP65
- Protection rating (IK): IK09
- Dimensions / length: 133 mm x 65 mm x 23 mm

Product data sheet

1979 N-82

EAN-No. 4000896227211



Order Number

1979 N-82