

# Product data sheet


## 6295-1 CT CAL

EAN-No. 4000896193110



Length: 962 mm · Torque range min-max: 200 – 500 Nm · Accuracy: 2 % ·  · Mit DAkkS-Kalibrierschein



- Torque wrench **with DAkkS calibration certificate**
- Plug connection for holding insert tools
- **Accuracy  $\pm 2\%$  of the scale value** (in the direction of actuation)  
Can be used for right-hand and left-hand threads by turning the insert tool
- Safe:
  - Haptic (close-gap release)
  - Audible ("click" sound)
- With calibration certificate and serial number
- Safe and fast adjustment of the desired torque value by turning the handle
- Secure storage in safe box with inspection window
- **2-component handle** for improved feel
- Simplified locking for adjusting the torque value
- Viewing window for visual checking of the locking
- Knob for additionally locking the set value
- 4 coloured coding rings (red, yellow, green, black) for markings in the case of personalisation or special workflows
- DIN EN ISO 6789-2:2017
- Made in Germany
- Output: 
- Dimensions / length: 962 mm
- For manual operation
- Torque range min-max: 200 – 500 Nm
- Accuracy: 2 %
- Scale Graduation (Nm): 2.5 Nm
- Effective torque wrench length min.-max. l1 mm: 937.20 – 925.20 Nm
- Actuating force min.-max. kg: 21.8 – 55.1 kg
- Inside micrometre of the adjusting tool l2: 44 mm
- Head Width b: 35.5 mm
- **No more turning back:** Continuous long-term tests on the 5000 series and 6000 series of HAZET torque wrenches have demonstrated that turning them back to the smallest scale value is not required

**DAkkS calibration certificate** for the professional user, especially for:

- Aviation industry
- Automobile industry
- New-energy, wind turbines, offshore wind farms
- Petrochemical industry (oil/gas)

Documented traceability guarantees complete verifiability

SYSTEM 6200-1 CT insert torque wrench · 2 – 500 Nm · with insert square · accuracy  $\pm 2/4\%$

# Product data sheet

**6295-1 CT CAL** EAN-No. 4000896193110



Order Number

6295-1 CT CAL