

# Product data sheet

**6391-12** EAN-No. 4000896**027026**



Length: 124 mm · Torque range min-max: 2 – 12 Nm · Accuracy: 2 % ·



- Particularly easy to use thanks to short design
- Universal application thanks to connection for insert tools
- **Accuracy  $\pm 2\%$  (6391-10: 6%) of the preset value** (in direction of actuation)  
Can be used for right-hand and left-hand threads by turning the insert tool
- Plug connection, for holding insert tools
- **Permanently adjustable value**
- Especially suitable for application in industrial series fabrication
- Adjusting the desired torque value with adjustment wrench 6399 in conjunction with HAZET torque tester 7901E · 7902E · 7903E or another suitable device.  
**All wrenches of this series (HAZET 6391-6392) are without an adjusting scale**
- With calibration certificate and serial number
- DIN EN ISO 6789-2:2017
- Made in Germany
- Output:
- Dimensions / length: 124 mm
- Net weight: 0.15 kg
- For manual operation
- Torque range min-max: 2 – 12 Nm
- Accuracy: 2 %
- Effective torque wrench length min.-max. l1 mm: 121.00 – 121.00 Nm
- Actuating force min.-max. kg: 1.7 – 10.1 kg
- Inside micrometre of the adjusting tool l2: 19.5 mm
- Head Thickness a: 17 mm
- Head Width b: 22 mm

SYSTEM 6300 CT industrial insert torque wrench · 2 – 320 Nm · with insert square · fixed adjustable value · accuracy  $\pm 2\%$

**Order Number**

6391-12