

Product data sheet

4904-12 EAN-No. 4000896236237



79.5 – 133 mm



- Compact HAZET design enables spring replacement with remarkable time savings
- Universal application on almost all passenger cars
- Tensioning jaw · span width 79.5 – 133 mm
- **Anti-rotation device** for lower tensioning jaws integrated in the base component **reduces the outer diameter to 32 mm**
- Pendulum 6-point head for **uniform distribution of power**
- Integrated **anti-rotation device** for upper clamping plates
- One-sided counterholder for the spindle by hexagon on top, e.g. with combination wrench HAZET 600N-13
- Removal and installation of **springs with small coil spacing**, e.g. for the **MINI** Cooper S (third generation) · **VW** Passat (B8)
- **Span 120 mm**
- **Loading up to 31,000 N** – work safely on electric and hybrid vehicles
- **GS mark for tested safety** – tested with at least **four-fold safety against breakage**
- 17° angular movement of the tensioning jaws ensures removal of **C-shaped (bent) springs**, e.g. **AUDI** A4 (B9) · **VW** Golf 7
- **Internal and external guidance** the clamping plates prevents the spring from sliding out
- All clamping plates included, reusable, replaceable **plastic protective pads**
- Tested on vehicles of the following manufacturers:
AUDI · BMW · CITROËN · FIAT · FORD · HYUNDAI · KIA · MAZDA · MERCEDES-BENZ · MINI · OPEL · PEUGEOT · RENAULT · SEAT · ŠKODA · TOYOTA · VW

Highlights:

- Easy handling for just one user
- Eliminates time-consuming work associated with most spring removal:
 - Removal of axle parts unnecessary
 - Axle alignment no longer necessary
 - Removal and installation possible in just a few minutes on each side
- Made in Germany
- Diameter (min-max): 79.5 – 133 mm

Order Number

4904-12