

# Product data sheet

**4904-12** EAN-No. 4000896236237



79.5 – 133 mm



- Compact HAZET design enables spring replacement with remarkable time savings
- Universal application on almost all passenger cars
- Tensioning jaw · span width 79.5 – 133 mm
- Anti-rotation device for lower tensioning jaws integrated in the base component reduces the outer  $\varnothing$  to only 32 mm thanks to compact design
- Pendulum hexagonal head for equal force distribution with integrated anti-rotation protection for upper tensioning jaws
- One-sided counterholder for the spindle made possible by hexagon on top, e.g. with combination wrench HAZET 600N-13
- Removal and installation of springs with small coil spacing, e.g. for the **MINI** Cooper S (third generation) · **VW** Passat (B8)
- Extension of the span to 120 mm and an increase of the maximum load for increasing vehicle weights (electric and hybrid vehicles), for safe working up to 31,000 N → Tested with at least four-fold safety against breakage (GS mark of tested safety)
- 17° angular movement of the tensioning jaws now ensures removal of C-shaped (bent) springs, e.g. on the **AUDI** A4 (B9) · **VW** Golf 7
- Internal and external guidance of the tensioning jaws prevents the spring from sliding out
- All tensioning jaws included, reusable, replaceable plastic protective pads
- Tested on vehicles of the following manufacturers:  
**AUDI · BMW · CITROËN · FIAT · FORD · HYUNDAI · KIA · MAZDA · MERCEDES-BENZ · MINI · OPEL · PEUGEOT · RENAULT · SEAT · ŠKODA · TOYOTA · VW**

#### Highlights:

- Easy handling for just one user
- Eliminates time-consuming work associated with most spring removal:
  - Removal of axle parts unnecessary
  - Axle alignment no longer necessary
  - Removal and installation possible in just a few minutes on each side
- Made in Germany
- Diameter (min-max): 79.5 – 133 mm

Order Number

4904-12