

Product data sheet

9013 MTT

EAN-No. 4000896258062



Loosening torque maximum [Nm]: 1890 Nm · $20 \frac{3}{4}$ · Powerful twin hammer mechanism



Application:

Operation of tight-fitting screw connections in narrow installation spaces with low workload in daily operation

- Loosening torque maximum [Nm]: 1890 Nm
- Exhaust air is guided through the handle downwards
- Reduced vibrations
- Easy handling
- Reduced workload due to low weight and handy dimensions
- Long service life and high efficiency in industrial and automotive applications
- Compact design, optimised for work in confined spaces
- **20 mm ($\frac{3}{4}$) impact wrench in 12.5 mm ($\frac{1}{2}$) housing size**
- HAZET Twin Turbo technology – high torques with compact design
- 8-blade air motor with 25% higher impact performance ensures maximum torque
- Easy to use
- Powerful twin hammer mechanism
- Air connection inlet: inside thread (IG) 12.91 mm ($\frac{1}{4}$)
- Coupler plug: Nominal size 7.2 (included)
- Recommended torque: 900 Nm
- Hose diameter (recommended): 10 mm
- Working pressure (bar): 6.3
- Sound power level: 110.3 db(A) Lp W
- Vibration acceleration: 11.39 m/s²
- Loosening torque (maximum) determined with screw size M: 26
- Forward and reverse: three-stage (forward), single-stage (reverse)
- Cold insulated handle
- Output: $20 \frac{3}{4}$
- Net weight: 1.7 kg
- For impact operation
- Tightening torque maximum [Nm]: 1300 Nm

Product data sheet

9013 MTT

EAN-No. 4000896258062



- Loosening torque maximum [Nm]: 1890 Nm
- Sound pressure level: 99.3 dB(A) Lp A
- Revolutions per minute: 8000
- Air requirement: 150 l/min (2.5 l/sec)

Handle	Cold insulated handle
Order Number	9013 MTT