

Product data sheet


6282-1 CT CAL

EAN-No. 4000896193080



Length: 240 mm · Torque range min-max: 4 – 40 Nm · Accuracy: 2 % ·  · Mit DAkkS-Kalibrierschein



- Torque wrench **with DAkkS calibration certificate**
- Plug connection for holding insert tools
- **Accuracy $\pm 2\%$ of the scale value** (in the direction of actuation)
Can be used for right-hand and left-hand threads by turning the insert tool
- Safe:
 - Haptic (close-gap release)
 - Audible ("click" sound)
- With calibration certificate and serial number
- Especially slim design thanks to spring-loaded puller sleeve for locking the setting values
- Safe and fast adjustment of the desired torque value by turning the handle
- DIN EN ISO 6789-2:2017
- Made in Germany
- Output: 
- Dimensions / length: 240 mm
- For manual operation
- Torque range min-max: 4 – 40 Nm
- Accuracy: 2 %
- Scale Graduation (Nm): 0.4 Nm
- Effective torque wrench length min.-max. l1 mm: 219.40 – 205.90 Nm
- Actuating force min.-max. kg: 1.9 – 19.8 kg
- Inside micrometre of the adjusting tool l2: 19.5 mm
- Head Thickness a: 17 mm
- Head Width b: 22 mm

Not according to DIN, as the maximum torque value of the square specified in the standard 6789-1:2017 is exceeded

- **No more turning back:** Continuous long-term tests on the 5000 series and 6000 series of HAZET torque wrenches have demonstrated that turning them back to the smallest scale value is not required

DAkkS calibration certificate for the professional user, especially for:

- Aviation industry
- Automobile industry
- New-energy, wind turbines, offshore wind farms
- Petrochemical industry (oil/gas)

Documented traceability guarantees complete verifiability

SYSTEM 6200-1 CT insert torque wrench · 2 – 500 Nm · with insert square · accuracy $\pm 2/4\%$

Order Number

6282-1 CT CAL