

# Product data sheet

## 5121-3 CT CAL

EAN-No. 4000896243167



Length: 421 mm · Torque range min-max: 20 – 120 Nm · Accuracy: 3 % ·  $\frac{1}{2}$  · Mit DAkkS-Kalibrierschein



- User-friendly reversible ratchet
- Torque wrench **with DAkkS calibration certificate**
- **SYSTEM 5000-3 CT** –
- **Accuracy  $\pm 3\%$  of the scale value** (in direction of actuation for right-hand tightening) (5107-3CT  $\pm 4\%$  accuracy of scale value)
- For left-hand tightening, use our torque wrenches with insert tool
- Safe:
  - Haptic (close-gap release)
  - Audible ("click" sound)
- Designed for rough workshop use
- Wide range of applications for controlled screw tightening in tyre service, bicycle, passenger car and commercial vehicle applications as well as various applications in trade and industry
- Optimised sealing ring to protect against debris
- Ratchet repair set for customer-oriented self-assembly enables decades of use
- Handle with better grip for easier power transmission
- Adjustment aid with detent points for optimised operator guidance ensures safe and fast adjustment of the desired torque value by turning the handle
- Safe locking of the setting values by latching function on the rotary assembly
- Rotary assembly in triangular form prevents uncontrolled rolling
- Lock symbols indicate the respective locking status
- Can be attached to the cable loop through openings on the locking rotary assembly
- Easy-to-read, high-contrast scale
- Permanent readability due to laser marking on the scale bush
- Integrated shift lever  
**5121-3CT – 5123-3CT:** shift lever with idle function – reduces risk of injury and malfunction
- With calibration certificate and serial number
- Delivery in sturdy Hexa plastic box
- DIN EN ISO 6789-2:2017, DIN 3120, ISO 1174-1
- Made in Germany
- Output:  $\frac{1}{2}$
- Dimensions / length: 421 mm
- For manual operation
- Torque range min-max: 20 – 120 Nm
- Accuracy: 3 %
- Scale Graduation (Nm): 1 Nm
- Actuating force min.-max. kg: 6.1 – 38.0 kg

# Product data sheet

## 5121-3 CT CAL

EAN-No. 4000896243167



- Number of teeth: 32 (Opening angle 11.25°)
- Head Thickness a: 19.6 mm
- Head Width b: 44 mm
- **No more turning back:** Continuous long-term tests on the 5000 series and 6000 series of HAZET torque wrenches have demonstrated that turning them back to the smallest scale value is not required

**DAkkS calibration certificate** for the professional user, especially for:

- Aviation industry
- Automobile industry
- New-energy, wind turbines, offshore wind farms
- Petrochemical industry (oil/gas)

Documented traceability guarantees complete verifiability

SYSTEM 5000-3 CT workshop torque wrench · 1 – 800 Nm · with reversible ratchet · accuracy  $\pm 3 / 4 \%$

**Order Number**

5121-3 CT CAL