

Product data sheet

6293-1 CT

EAN-No. 4000896026173



Length: 625 mm · Torque range min-max: 60 – 320 Nm · Accuracy: 2 % ·



- Plug connection for holding insert tools
- **Accuracy $\pm 2\%$ of the scale value** (in the direction of actuation)
Can be used for right-hand and left-hand threads by turning the insert tool
- Safe:
 - Haptic (close-gap release)
 - Audible ("click" sound)
- With calibration certificate and serial number
- Safe and fast adjustment of the desired torque value by turning the handle
- Secure storage in safe box with inspection window
- DIN EN ISO 6789-2:2017
- Made in Germany
- Output:
- Dimensions / length: 625 mm
- Net weight: 1.25 kg
- For manual operation
- Torque range min-max: 60 – 320 Nm
- Accuracy: 2 %
- Scale Graduation (Nm): 2 Nm
- Effective torque wrench length min.-max. l1 mm: 592.00 – 573.80 Nm
- Actuating force min.-max. kg: 10.3 – 56.8 kg
- Inside micrometre of the adjusting tool l2: 38.5 mm
- Head Thickness a: 23 mm
- Head Width b: 30 mm
- **No more turning back:** Continuous long-term tests on the 5000 series and 6000 series of HAZET torque wrenches have demonstrated that turning them back to the smallest scale value is not required

SYSTEM 6200-1 CT insert torque wrench · 2 – 500 Nm · with insert square · accuracy $\pm 2/4\%$

Order Number

6293-1 CT